

Dräger Saver CF15

The Saver range of Emergency Escape Breathing Apparatus has been designed using the latest technologies available whilst still bearing in mind our three leading principles; reliability, quality and ease of use. The Saver CF constant flow emergency escape breathing apparatus allows safe, effective and uncomplicated escape from hazardous environments with the minimum of user training.



Dräger Saver CF15, with storagebox

Designed with one thing in mind, to save lives

Automatic activation

The unit is automatically activated on opening the carrying bag and can be simply re-set in the event of false alarm.

Long life neck seal

The air hood neck seal is ozone resistant ensuring high levels of protection, even after storage.

High visibility

The unit is contained in an instantly recognisable orange carrying bag, incorporating photo luminescent panels allowing the unit to be seen at very low ambient light and visibility levels.

Easy inspection

The cylinder contents gauge is clearly visible without any dismantling or adjustments to the unit due to a transparent viewing window located on the side of the bag. This allows for quick and simple cylinder contents inspection.

Made to measure

The Saver CF has been especially designed to be as easy to don as is possible, regardless of face shape or size and is suitable for users with glasses or facial hair.

Design

Utilises a simple fail-safe reducer system with excellent flow characteristics giving a consistent air flow rate at all cylinder pressure levels. The combined diffuser and exhalation valve account for excellent air supply combined with a very streamlined hood profile. The easy to don flame retardant hood incorporates a wide visor for enhanced peripheral vision and a long life ozone resistant neck seal.

The Saver CF is extremely compact in design providing greater freedom of movement.

Carrying bag

The high visibility orange carrying bag incorporates photo luminescent panels, is interchangeable for either chest bag or bandoleer positions, washable, flame retardant and allows water to self-drain.

Low contents warning

A warning whistle sounds when the unit is nearing the end of its air supply.

Optional: Storage box

Storage box for EEBD complete with photo luminescent sign.

TECHNICAL SPECIFICATIONS

Dräger Saver CF15	
Dimensions	490 x 160 x 250 mm
Weight	5.2 kgs
Max. pressure	200 bar
Working temperature	-15°C to 60°C
Storage box	
Dimensions	740 x 280 x 220 mm (l x w x d)
Weight	1.3 kgs