

## Fire Resistant Safety Belt

Fireman's work positioning belt is especially designed for fire brigades. They are exclusively intended to prevent falls from a height in hazardous areas.



### Fire Resistant Safety Belt

To prevent falls from a height

#### Features

When putting on the fireman's work positioning belt, the belt itself is wrapped around the body and closed by pulling the webbing end through the alloy frame, going back with it through the two-pin buckle and hooking the metal inserts into this. After that the webbing end is pulling through and fixed by the fitted webbing loops. The belt has to fit the body tightly.

#### Optional

The belt is optional equipped with carabiners with screw locking devices or Twistlocks. The multifunctional eye on the carabiner snaphook of the fireman's work positioning belt is a special feature for fire brigades and is intended exclusively for use with trained personnel. This multifunctional eye is for guiding loads to upper or lower levels.

#### Usage

The fixed lanyard is used for work place positioning (positioning or restraint purposes) and attaches to the anchor point by a carabiner snaphook. The anchor point has to be at or above waist level and should bear a minimum load of 10 kN according to EN 795. In fall hazardous areas the lanyard must always be tensioned to limit the free room of movement to maximum 0,6 meters.

#### Important

A fireman's work positioning belt is definitely not a full body harness. The positioning belt should be owned by the user individually and is only allowed to be used by seriously trained personnel.

### TECHNICAL SPECIFICATIONS

Carbine	Twistlock
Weight	1.030 gr
Approvals	DIN 14927

### ORDER INFORMATION

Description	Unit Sales	Articlenr
Fire Resistant Safety Belt, size 3	1	SG03848