

## Dräger 9 liter AB composite foam extinguisher (stored pressure)



**Dräger 9 liter AB composite foam extinguisher**  
Stored pressure

The revolution in portable fire extinguishers: composite extinguishers are the latest development in the quest for durable corrosion resistant and low maintenance extinguishers. The extinguishers have EN3, CE and MED certification and a lifetime of 20 years. Another unique feature: the extinguishing medium in these units needs to be replaced every 10 years as per manufacturer specification. Foam extinguishers cover type A and B fires.

### General description

The red outer HDPE mantle houses a pressure vessel which is manufactured out of HDPE. The valve is supplied in gunmetal. Hose clips, squeeze for action handle and carrying handle are supplied in stainless steel. Due to these material and construction choices replacement of the extinguisher caused by corrosion, scratches and dents belong to the past. Resulting into lower lifetime costs. In addition the extinguisher will remain in good condition, offering greater reliability for the user when being deployed in firefighting tasks. These extinguishers are 100% recyclable, reducing waste output at the end of its service life.

### AB foam

AB foam is suitable for fire extinguishing of substances in fire class A (containing carbons) and fire class B (flammable liquids). An additional feature is that the foam is not

conductive to electricity. The foam can be used to a maximum voltage of 1000 V and at a distance of at least 1 meter.

### Applications

These extinguishers are extremely suitable for harsh (outdoor, saline) conditions as found on offshore installations, marine application, yachts and moist (production) spaces.

### Features

- 10 year manufacturer guarantee
- replacement of foam once every 10 years
- durable and corrosion free
- reliable and ultra-strong composite material
- 100% UV resistant
- ± 15% lighter than conventional extinguishers
- cost reducing
- better overview of cost control
- environmentally friendly
- 100% recyclable product

## TECHNICAL SPECIFICATIONS

Manufacturer / Model	Britannia / P50-9F
Extinguisher	Portable foam fire extinguisher
Type	Stored pressure operated
Capacity	9 liter
Fire class / Rating	34A/183B
Propellant gas	Nitrogen
Discharge time	49 seconds
Throw length	7 meters
Working pressure	12 bar
Suitable for electrical equipment	Up to 1000 Volt
Extinguishing agent	Foam
Temperature range	+5°C to +60°C
Approx gross weight	11.7 kgs
Approx dispatch weight	12.7 kgs
Approx unit dimension	640 x 210 mm (H x D)
Color	Red (RAL3000)
Approvals	EN3, MED, CE, Rijkskeurmerk 2212/01

## Dräger 9 liter AB composite foam extinguisher (stored pressure)

### ORDER INFORMATION

Description	Unit Sales	Articlenr
Dräger 9 liter AB composite foam extinguisher (stored pressure)	1	01170221
Bracket for Composite powder extinguisher	1	18108025
Cover for fire extinguisher	1	18107002
GRP storage cabinet: DMO-35	1	03120114
Polyethylene fire extinguisher cabinet JBWE-70, red door	1	03130003